

# Pica Cube™ UV

Compact, square profile, ultra-violet LED spot luminaire with flicker-free 0 – 100% dim and dim to warm capability, spread lenses, and dimming and control accessories. Controllable via DMX or on-board menu.

## General

1. Luminaire shall be a compact square ultra-violet LED light, with a set of three spread lenses, 20°, 40°, 60°, dimming and control accessories, and optional optical control accessories. The luminaire shall be a Rosco Pica Cube™ UV with dimming and control accessories as manufactured by Rosco Labs, Inc.
2. Luminaire housing shall be 2.5 in x 2.5 in x 3.6 in (63.5 mm x 63.5 mm x 91 mm) and come in standard color of black.
3. Luminaire shall have a bracket for non-track installation, and a yoke for track installation.
4. Luminaire shall be powered and controlled with a Rosco 12-24 VDC power supply, Rosco Pica Portal, or Rosco track.
5. Luminaire shall be UL 2108 listed for low voltage lighting systems, and CSA 22.2 No. 9 listed for luminaires.

## Physical

6. Luminaire housing shall be constructed of an 1/8 in extruded aluminum wall with powder coating in white or black. The LED module shall be seated with Rosco proprietary copper heat sink and light mixing lens optics as designed by The Black Tank.
7. Luminaire shall be 2.5 in x 2.5 in x 3.6 in (63.5 mm x 63.5 mm x 91 mm) and when combine with bracket weigh no more than 0.9 lbs (0.41 kg).
8. Bracket shall attach to one side of the housing. Yoke shall attach to both sides of housing. Bracket and yoke shall be adjustable via locking knobs at point of attachment to side(s) of housing.
9. Power supply shall accept 100-240VAC input and shall provide 12-24VDC output.
10. The following shall be included:
  - a. Luminaire
  - b. Bracket
  - c. Set of symmetrical spread lenses in 20°, 40°, and 60°
  - d. 12-24 VDC Power supply, Rosco Pica Portal, or Data Track Adapter Assembly for track installation
11. Luminaire shall accept optional Rosco Barn Doors, Egg Crate Louvers or Top Hats for additional beam control.

## Optical

12. Output shall be 2700mW with a native beam angle of 8° (no lens).
13. Peak Wavelength of 365nm.
14. Lenses shall be symmetrical at 20°, 40°, and 60°.

# Pica Cube™ UV

## Environmental and Agency Compliance

15. Luminaire shall be compliant to FCC Class A Radiated and Conducted emissions for commercial and industrial use.
16. Luminaire shall be UL 2108 listed for low voltage lighting systems.
17. Luminaire shall be CSA 22.2 No. 9 listed for luminaires.
18. Luminaire shall be RoHS Compliant.
19. Luminaire shall be rated at IP20 for Indoor use only.

## Thermal

20. Luminaire shall operate in an ambient temperature range of -13° F min to 113° F max (-20° C min to 45° C max)

## Electrical

21. Luminaire shall be equipped with an external 12-24 VDC power supply, a Rosco Pica Portal, or a track mount kit.
22. Luminaire shall have the option of receiving data and power from a single Cat 5e feed using an RJ45 connector.
23. Luminaire shall consume no more than 24w.

## LED Emitters

24. Emitter shall be 1 x 365nm UV LED.
25. Peak 365nm.
26. Lumen Maintenance shall be 20,000 hours L90 @ 25°C.

## Control and Dimming

27. Luminaire shall be dimmable by DMX or via User Interface on the rear panel. Luminaire shall require 1 channel for 8-bit control, 2 channels for 16-bit control.
28. Dimming shall be flicker-free, 0 – 100%.
29. DMX control shall be achieved with the Rosco Preset Remote or any DMX controller.
30. Luminaire shall include DMX Out to enable daisy-chain control of multiple units.
31. Luminaire shall use PWM, adjustable between 4kHz and 16kHz for flicker-free dimming
32. Luminaire shall be compatible with optional data and non-data track adapters, including but not limited to Eutrac 1C/2C/3C, Juno, Halo, Lightolier.

## Specification Ordering Example

Product ordering information can be found at this URL: <https://www.rosco.com/product/pica-cube-uv>

The product numbers for ordering are listed below. When ordering for track mount specify Pica Cube DMX Data Track Adapter.

515 90200 1075	Pica Cube UV – Black
515 91110 0028	Pica Cube DMX Data Track Adapter – Black
515 91110 0029	Pica Cube DMX Data Track Adapter – White

If there are questions, contact Rosco Customer Service: [CTOrders@rosco.com](mailto:CTOrders@rosco.com)

# Table Specification for Pica Cube™ UV

Type ID	Qty	Description	Manufacturer	Alternate Manufacturer	Light Source / Power Source			Control
					Color Temp.	LED Type	Watts/Volts	
		Compact rectangular LED 2.5 in x 2.5 in x 3.6 in (63.5mm x 63.5mm x 91mm), with housing made of extruded aluminum with optical lens package	Rosco Labs		UV LED with peak 365nm	365nm UV emitters	24w	DMX via Cat 5e with RJ45 or Manual UI controllable, 0 – 100% flicker-free
Comments								
To be track mounted. To be controlled with Rosco Portal. To be set with remote DMX control.								