

Labtest U.S.A. Inc. 101 West 51st Street New York, NY 10001 Telephone (212) 868-7090 Fax (212) 967-2566

TEST REPORT

ROSCO LABORATORIES, INC. 36 Bush Avenue Port Chester, NY. 10573 Attn. Diane

REPORT NO. 83280

April 1, 2015

IDENTIFICATION SUBMITTED BY CLIENT

1 ROSCO DANCE FLOOR

FIRE RESISTANCE NFPA 701 - Small Scale

EVALUATION OF TEST RESULTS

The fabric submitted for testing <u>DOES</u> pass the flame resistance requirements when tested, as received, in accordance with procedures outlined in the National Fire Protection Association Standard 701. The fabric was tested in the original state only. The procedure does include testing after exposure (e.g. laundering, drycleaning, leaching or weathering) outlined in Chapter 8 of the NFPA Standard 701. The client may wish to take this into consideration.

IF YOU NEED ASSISTANCE IN INTERPRETING THESE TESTS RESULTS OR IF YOU HAVE ANY QUESTIONS, PLEASE FEEL FREE TO CALL: ALMA BURROWES OR FLORENCE SLATER

Test Reference 83280 JG



LABTEST U.S.A., INC.

Alma Burrowes

Director of Customer Service

-continued-

SUBJECT TO TERMS AND CONDITIONS ON BACK

Labtest U.S.A. Inc. 101 West 31st Street New York, NY 10001 Telephone (212) 868-7090 Fax (212) 967-2566

TEST REPORT

PAGE 2

REPORT NO. 83280

April 1, 2015

IDENTIFICATION SUBMITTED BY CLIENT

ROSCO DANCE FLOOR

TEST RESULTS

STATE OF SAMPLE: AS RECEIVED

END USE: _ - -

WARP			FILLING		
AFTERFLAME (SECONDS)	CHAR LENGTH (INCHES)	BURNING OF DRIPPINGS	AFTERFLAME (SECONDS)	CHAR LENGTH (INCHES)	BURNING OF DRIPPINGS
0.0	1.9	NONE	0.0	1.1	NONE
0.0	1.5	NONE	0.0	1.4	NONE
0.0	1.8	NONE	0.0	2.1	NONE
0.0	1.8	NONE	0.0	1.8	NONE
0.0	2.1	NONE	0.0	2.2	NONE

Average Char Length for Ten Specimens: 1.8 Inches

REQUIREMENTS

Afterflame** Length of Char*	Two seconds (Maximum) for any one specimen. Based on the fabric weight of $43.0~{\rm Oz./Yd^2}$.			
	$\frac{3.5}{4.5}$ Inch average for ten specimens (Maximum). $\frac{4.5}{4.5}$ Inch for any one specimen (Maximum).			
Burning of Drippings**	Residues which break or drip from any test specimen shall not continue to flame after reaching the floor of the test chamber.			

**EXCEPT FOR FABRIC WEIGHING LESS THAN 10 OZS/YD2 WITH END USE SPECIFIED AS DRAPERIES OR CURTAINS. AFTERFLAME DOES NOT APPLY BURNING OF DRIPPINGS: 2 SECONDS MAXIMUM.

*WEIGHT OF FABRIC BEING TESTED	MAXIMUM AVERAGE CHAR LENGTH FOR TEN SPECIMENS	
Over 10 Oz./Yd ² 6.1 - 10.0 Oz./Yd ² 6.0 Oz./Yd ² or Less	3.5 Inches 4.5 inches 5.5 Inches	4.5 Inches 5.5 Inches 6.5 Inches
Drapery & Curtains under 10 Ozs./Yd².	6.5 Inches	7.5 Inches